

◆玻璃纖維

			
型號	K-HS 0.3×1P	K-HS 0.6×1P	J-HS 0.6×1P
規格	素線級，單芯0.3	素線級，單芯0.6	素線級，單芯0.6
耐溫	0~200℃	0~200℃	0~200℃
			
型號	20-K-GG 0.81×1P	24-K-GG 0.51×1P	KEX-H 4/0.3×1P
規格	素線級，單芯(美)	素線級，單芯(美)	補償級，4芯0.3
耐溫	480~540℃	480~540℃	0~200℃
			
型號	KEX-H 7/0.3×1P	KEX-H 4/0.6×1P	KEX-H 7/0.6×1P
規格	補償級，7芯0.3	補償級，4芯0.6	補償級，7芯0.6
耐溫	0~200℃	0~200℃	0~200℃
			
型號	REX-H 7/0.3×1P	REX-H 4/0.6×1P	REX-H 7/0.6×1P
規格	補償級，7芯0.3	補償級，4芯0.6	補償級，7芯0.6
耐溫	0~200℃	0~200℃	0~200℃
			
型號	J-HS 7/0.3×1P	J-HS 4/0.6×1P	J-HS 7/0.6×1P
規格	素線級，7芯0.3	素線級，4芯0.6	素線級，7芯0.6
耐溫	0~200℃	0~200℃	0~200℃

❖ **訂購型號參考表**

