

## ❖ PVC

型號	K-GS 0.6×1P	K-GS 4/0.3×1P	KEX-G 4/0.3×1P
規格	素線級，單芯0.6	素線級，4芯0.3	補償級，4芯0.3
耐溫	0~105℃	0~105℃	0~105℃
型號	KEX-G 7/0.3×1P	KEX-G 4/0.6×1P	KEX-G 7/0.6×1P
規格	補償級，7芯0.3	補償級，4芯0.6	補償級，7芯0.6
耐溫	0~105℃	0~105℃	0~105℃
型號	TC-CA-G 4/0.3×1P	J-GS 7/0.3×1P	J-GS 4/0.6×1P
規格	素線級，4芯0.3	素線級，7芯0.3	素線級，4芯0.6
耐溫	0~105℃	0~105℃	0~105℃
型號	J-GS 7/0.6×1P	REX-G 4/0.6×1P	T-GS 7/0.3×1P
規格	素線級，7芯0.6	補償級，4芯0.6	素線級，7芯0.3
耐溫	0~105℃	0~105℃	0~105℃
型號	KEX-G-IS 7/0.3×1P	KEX-G-IS 4/0.6×1P	J-GS-IS 4/0.6×1P
規格	補償級，7芯0.3 金屬網內隔離	補償級，4芯0.6 金屬網內隔離	素線級，4芯0.6 金屬網內隔離
耐溫	0~105℃	0~105℃	0~105℃
型號	J-GS-IS 7/0.6×1P	REX-G-IS 4/0.6×1P	E-GS-IS 4/0.6×1P
規格	素線級，7芯0.6 金屬網內隔離	補償級，4芯0.6 金屬網內隔離	素線級，4芯0.6 金屬網內隔離
耐溫	0~105℃	0~105℃	0~105℃

❖ **訂購型號參考表**

