

## ❖金屬網線

			
型號	K-HS-SOS 0.6×1P	K-HS-OS 0.6×1P	J-H-SOS 0.6×1P
規格	素線級，單芯0.6	素線級，單芯0.6	素線級，單芯0.6
耐溫	0~200℃	0~200℃	0~200℃
			
型號	J-HS-OS 0.6×1P	K-HS-SOS 4/0.3×1P	K-HS-OS 4/0.3×1P
規格	素線級，單芯0.6	素線級，4芯0.3	素線級，4芯0.3
耐溫	0~200℃	0~200℃	0~200℃
			
型號	J-HS-SOS 4/0.3×1P		
規格	素線級，4芯0.3		
耐溫	0~200℃		
			
型號	KEX-H-SOS 4/0.6×1P	KEX-H-SOS 7/0.6×1P	KEX-H-SOS 7/0.3×1P
規格	補償級，4芯0.6 金屬網外隔離	補償級，7芯0.6 金屬網外隔離	補償級，7芯0.3 金屬網外隔離
耐溫	0~200℃	0~200℃	0~200℃
			
型號	KEX-G-SOS 4/0.6×1P	KEX-G-SOS 7/0.6×1P	J-HS-SOS 7/0.3×1P
規格	補償級，4芯0.6 金屬網外隔離	補償級，7芯0.6 金屬網外隔離	素線級，7芯0.3 金屬網外隔離
耐溫	0~105℃	0~105℃	0~105℃
			
型號	J-HS-SOS 7/0.6×1P	REX-H-SOS 4/0.6×1P	REX-H-SOS 7/0.6×1P
規格	素線級，7芯0.6 金屬網外隔離	補償級，4芯0.6 金屬網外隔離	補償級，7芯0.6 金屬網外隔離
耐溫	0~105℃	0~200℃	0~200℃

❖ **訂購型號參考表**

